

Robust, Reliable, Proven Tape Backup

RELIABILITY
RELIABILITY
RELIABILITY

Features and Benefits

- **Advances the Quantum DLTape standard**—Read and write backward compatible with all DLTape formats
- **Higher performance**—6 megabytes per second native transfer rate with 40 gigabytes native capacity
- **Reliability**—Recording head life of 50,000 hours, media durability of 1,000,000 media passes, and MTBF of 250,000 hours at 100% duty cycle

The Industry Standard

The Quantum DLT 8000 tape drive system advances the standard in tape backup with improvements to capacity, performance, and cost of ownership while maintaining compatibility with a worldwide installed base of more than one million DLTape™ drives. The Quantum DLT 8000 tape drive will decrease your data backup time, give you the flexibility to scale to a wide range of backup applications, and protect your investment in previous generations of DLTape technology.

Through a number of design and technological innovations, the Quantum DLT 8000 tape drive delivers higher performance, greater capacity, increased reliability, and more functionality at a better price. For example, the Quantum DLT 8000 provides a native storage capacity of 40 gigabytes (GB) and a native transfer rate of 6 megabytes per second (MB/sec). This represents a 15 percent higher capacity and 20 percent

faster throughput than the Quantum DLT 7000 tape drive. To ensure superior accuracy, the Quantum DLT 8000 recording head boasts an average life of 50,000 hours. In fact, the Quantum DLT 8000 tape drive is rated at 250,000 hours MTBF at 100 percent duty cycle, which is 25 percent greater than previous DLTape products. The Quantum DLTape system is also economical and incredibly reliable, with a shelf life of 30 years and a working life of one million passes. By offering a high level of performance at an exceptional price, the Quantum DLT 8000 makes tape backup practical and affordable for a wide range of applications, including mid-range computers, network servers, high-end workstations, and mainframe environments running UNIX, NetWare, Microsoft Windows NT, LINUX, or proprietary operating systems.

When you're looking for quality, performance, reliability, and value in tape backup, look to Quantum first.



Specifications

Performance Specifications

Sustained Transfer Rate (MB/sec)	
Native	6
Compressed (up to)	12 ¹
Burst Transfer Rate (MB/sec)	
Synchronous	20
Asynchronous	12
Formatted Capacity (GB)	
Native	40
Compressed	80 ¹
Average File Access (sec)	60
Interface	SCSI-2 Fast/Wide (SE/LVD or HVD)

Tape Format Specifications

Recording Format	208 track serial serpentine
Recording Density	98 kbits per inch
Track Density (tpi)	416
Encoding Method	RLL 2,7
Data Compression	DLZ

Reliability Specifications

MTBF (hours)	250,000 at 100% duty cycle
Head Life (hours)	50,000
Media Durability	1,000,000 passes (15,000 uses)
Uncorrected Error Rate	1 x 10 ¹⁷ bits read
Undetected Error Rate	1 x 10 ²⁷ bits read
Warranty (years)	3

Physical Specifications

Dimensions—inches (mm)	Table Top	Rack Mount ²
	Width	5.7 (144.8)
	Length	9.0 (228.6)
	Height	3.25 (82.5)
Weight—pounds (kg)	14 (6.35)	6 (2.9)

Environmental Limits

Operating	
Temperature °F (°C)	50 to 104 (10 to 40)
Non-Condensing Humidity (%)	20 to 80
Altitude (ft. maximum)	40,000
Non-Operating	
Temperature °F (°C)	-40 to 151 (-40 to 66) excluding media
Non-Condensing Humidity (%)	10 to 95
Altitude (ft. maximum)	40,000

Power Specifications

Voltage (V)	+5, +12
Power Consumption (W)	28

Media/Format Compatibility

DLTape III	10 GB native capacity
DLTape IIIXT	15 GB native capacity
DLTape IV	20, 35, and 40 GB native capacities
Read/write compatible with all previous DLTape formats	
DLTape Cleaning Cartridge	20 uses

Tape Life

Archive Storage	More than 30 years with less than 5% loss in demagnetization (at 20°C and 40% non-condensing humidity)
Durability	Average 1,000,000 head passes in typical office/computer environment

Quantum DLTape Media Cartridges

Approved for use in all DLTape drives, Quantum DLTape half-inch cartridges are backed by a limited lifetime warranty.



For more information about Quantum's quality products, call toll-free: 1.800.624.5545 in the U.S.A. and Canada, or visit www.quantum.com and www.dlftape.com

Quantum.
DLT 8000

Quantum Corporation

500 McCarthy Boulevard
Milpitas, California 95035
U.S.A.
1.800.624.5545

Quantum Peripheral Products S.A.

ICC Building D
20 Route de Pre-Bois
1215 Geneva
Switzerland
41.22.929.7600

Quantum Asia-Pacific Pte. Ltd.

9 Temasek Boulevard
#24-00/Suntec City Tower 2
Singapore 038989
65.334.0880

Quantum Peripherals Japan

Shinjuku Square Tower 4F
6-22-1 Nishi-Shinjuku
Shinjuku-ku, Tokyo, 163-11
Japan
81.3.5321.7900

Specifications subject to change without notice.

©1999 Quantum Corporation. All rights reserved. Quantum and the Quantum logo are trademarks of Quantum Corporation, registered in the U.S.A. and other countries. DLTape and the DLTape logo are trademarks of Quantum Corporation. Products mentioned herein are for identification purposes only and may be trademarks or registered trademarks of their respective companies.

Printed in the U.S.A. on recycled paper 20K DF/CRFTSMN DLT80899

¹ Actual transfer rate and capacity will vary depending on data. ² Excluding bezel.